



NOTES

1. THE BARRIER SHALL BE CONSTRUCTED USING CONCRETE MIX NO.6 CONTINUOUSLY PLACED.
2. THE BARRIER SHALL BE CAST USING THE FIXED FORM OR THE SLIP FORM CONSTRUCTION METHOD.
3. ALL REINFORCEMENT BARS, INCLUDING ENDS, SHALL BE EPOXY COATED. ALL BAR LAPS TO BE 30 BAR DIAMETERS. TIE BARS TOGETHER. ALL BARS SHALL BE ASTM A 615 GRADE 60.
4. SPACING OF CONTRACTION JOINTS SHALL BE 20 FEET REGARDLESS OF CONSTRUCTION METHOD.
5. COST OF LABOR, ALL REINFORCEMENT, DRILLED HOLES, GROUT, EQUIPMENT, ETC., SHALL BE INCIDENTAL TO THE CONTRACT UNIT PRICE PER LINEAR FOOT FOR 42 INCH F SHAPE CONCRETE TRAFFIC BARRIER SINGLE FACE CONSTRUCTED ON EXISTING CONCRETE PAVEMENT.
6. TO BE USED AS FREE STANDING BARRIER ONLY (NO BACKING).
7. TOLERANCES IN DIMENSIONS SHOWN SHALL BE WITHIN 1/4".
8. CONDUIT: IF REQUIRED REFER TO STD. MD 648.50 FOR LOCATION.
9. WHEN BARRIER IS CONSTRUCTED USING THE SLIP FORM METHOD DIAGONAL NO.4 BARS ARE REQUIRED. SEE STD. MD 648.49.

SPECIFICATION 604	CATEGORY CODE ITEMS										
APPROVED	<i>Kirk G. McCall</i> DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT										
SHA State Highway Administration	<table> <tr> <td>APPROVAL • SHA REVISIONS</td><td>APPROVAL • FEDERAL HIGHWAY ADMINISTRATION</td></tr> <tr> <td>APPROVAL 3-1-01</td><td>APPROVAL 3-28-01</td></tr> <tr> <td>REVISED 10-1-01</td><td>REVISED</td></tr> <tr> <td>REVISED</td><td>REVISED</td></tr> <tr> <td>REVISED</td><td>REVISED</td></tr> </table>	APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION	APPROVAL 3-1-01	APPROVAL 3-28-01	REVISED 10-1-01	REVISED	REVISED	REVISED	REVISED	REVISED
APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION										
APPROVAL 3-1-01	APPROVAL 3-28-01										
REVISED 10-1-01	REVISED										
REVISED	REVISED										
REVISED	REVISED										

Maryland Department of Transportation
STATE HIGHWAY ADMINISTRATION
 STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES
42 INCH F SHAPE CONCRETE
TRAFFIC BARRIER SINGLE FACE CONSTRUCTED
ON EXISTING CONCRETE PAVEMENT
STANDARD NO. MD 648.55